





Right angle torch

Light, small and easy to operate. It incorporates our famous Power LEDEngine optics, including 3 LEDs (spot, flood and step light options). It easily adapts to the firefighter's tunic.



- Power LEDEngine optics with 3 LEDs
- Spot, flood and stroboscopic options
- Step Lighting System: a light beam projected directly into the ground to illuminate the path
- High and low intensity modes
- Indication of the light duration and battery level
- Ring and spring clip in the back
- Neodymium magnet optional
- Photoluminescent bezel optional

2 versions: L-90POWER (3x alkaline AA) L-90RPOWER (Li-ion battery)

ATEX II 1G Ex ia IIC T4 Ga 2D Ex ib IIIC T135°C Db

ATFX I M1 Fx ia I Ma GAS ZONE 0 | 1 | 2 DUST ZONE 21 22

Ingress protection: IP67

Weight: L-90POWER: 340 g (alkalines included) L-90RPOWER: 300 g (battery included)

Measures (LxWxH): 73x71x158 mm

Autonomy: Normal mode: L-90POWER: > 10 h / L-90RPOWER: 4 h Saving mode: L-90POWER: > 20 h / L-90RPOWER: 18 h

Torch body material: Thermoplastic resine with high resistance to the impacts, extreme temperatures and corrosive substances

Lighting source: L-90POWER High: 300 lm / Saving mode: 90 lm L-90RPOWER High: 340 lm / Saving mode: 90 lm

On/Off button: Made of soft touch material, it's placed on the top to guarantee easy finding and pushing with gloves


Battery level: the button lights up (green or red) to inform about the battery capacity

Chargers for 1, 2, 3 or 5 torches















ww.adalit.com

